

LUM INARIA A LASKA LED / LUM INAIRE A LASKA LED / A LASKA LED LUM INAIRE

ILAKLED

Luminaria ensayada por / Luminaire testé par / Luminaire tested by:

Applus[®] / EN-60598

Luminaria certificada por / Luminaire certifié par / Luminaire certified by:




ILAKLED30AC230



Fijación lateral / Fixation latérale /
Fixing: Side


Cuerpo: Inyección de aluminio.
Corps: Aluminium injecté.
Body: Injected aluminium.



Fijación: Lateral - Top mediante tubo.
Fixation: Installation latérale-top.
Fixing: Top or side fitting tube.

OPCIONAL: COLORES
EN OPTION: COULEURS
OPTIONAL: COLOURS

MEDIDAS / DIMENSIONS / SIZES				
Ref.	A	B	C	D
ILAKLED30S	560	260	115	Ø48-60
ILAKLED30S	560	260	115	Ø48-60
ILAKLED68	750	280	110	Ø48-60
ILAKLED90	880	360	120	Ø60-76
ILAKLED120	880	360	120	Ø60-76
ILAKLED160	985	360	120	Ø60-76



Una familia completa, con potencias de 30w a 160w
Une famille complète pour des puissances de 30 à 160 Watt
A full range from 30W to 160W




Compartimento de LEDs separado de la fuente de alimentación, con disipadores de calor independientes
Compartment LED séparé du compartiment électro - nique, Vaste radiateur externe
LED compartment separated from the power source featuring independent heat coolers



Rótula orientable en las versiones de 60w, 90w, 120w y 160w.
Rotule orientable sur les versions de 60W et supérieures
Adjustable joint in the following models: 60W, 90W, 120W and 160W



LED



Ref.	P [W]	N LEDs	[lm]	TC [K]	I [mA]	Input V [V]		IP		IK		Cx	ULOR	Lifetime
														
ILAKLED30S	30 W	24	2400 lm	4000 K	350 mA	24 V DC	No	IP66	IP66	IK09	-	0,048 m2	<1%	50000 h
ILAKLE- D30AC230	30 W*	24	2400 lm	4000 K	350 mA	100 - 277 V 50/60 Hz	No	IP66	IP66	IK09	-	0,048 m2	<1%	50000 h
ILAKLED68	60 W*	54	5000 lm	4000 K	350 mA	100 - 277 V 50/60 Hz	No	IP66	IP66	IK09	0° - 5° - 10° - 15°	0,065 m2	<1%	50000 h
ILAKLED90	90 W*	80	7800 lm	4000 K	350 mA	100 - 277 V 50/60 Hz	No	IP66	IP66	IK09	0° - 5° - 10° - 15°	0,092 m2	<1%	50000 h
ILAKLED120	120 W*	110	10900 lm	4000 K	350 mA	100 - 277 V 50/60 Hz	No	IP66	IP66	IK09	0° - 5° - 10° - 15°	0,092 m2	<1%	50000 h
ILAKLED160	160 W*	140	13740 lm	4000 K	350 mA	100 - 277 V 50/60 Hz	No	IP66	IP66	IK09	0° - 5° - 10° - 15°	0,11 m2	<1%	50000 h
5,2 / 5,2 / 9,5 / 14,4 / 14,9 / 17,2 Kgs														
* Dimming: PLC; 1-10 V; DALI; TIMER														